


Geluidsdemper

Sinterbrons-geluidsdemper



Werkdruk : Max. 16 bar
Werktemperatuur : Max. 200° C



Geluidsdemper korte versie (schroevendraaiermontage)

Model	Aansluiting G	A	B	C	CA-nummer
564-2	1/4	6	12	13	59/41/0241
564-3	3/8	7	15	17	59/41/0242
564-4	1/2	10	18	21	59/41/0243



Geluidsdemper, uit sinterbrons, vlakke versie, met inwendige aansluiting - moermontage

Model	Aansluiting G	SW	A	B	C	CA-nummer
565-0	M 5	-	-	8	4	59/41/0244
565-1	1/8	13	-	10	11	59/41/0245
565-2	1/4	16	-	11	14	59/41/0246
565-3	3/8	19	-	12	17	59/41/0247
565-4	1/2	24	-	13	22	59/41/0248



Geluidsdemper, uit sinterbrons, vlakke versie, met uitwendige aansluiting - boutmontage

Model	Aansluiting G	SW	A	B	C	CA-nummer
569-0	M 5	8	4	8	6	59/41/0249
569-1	1/8	13	6	13	11	59/41/0250
569-2	1/4	16	8	16	14	59/41/0251
569-3	3/8	19	9	18	17	59/41/0252
569-4	1/2	24	11	20	22	59/41/0253



Geluidsdemper, uit sinterbrons, met zeskant moer

Model	Aansluiting G	SW	A	B	C	CA-nummer
567-1	1/8	13	6	28	8	59/41/0254
567-2	1/4	17	8	34	12	59/41/0255
567-3	3/8	22	10	36	15	59/41/0256
567-4	1/2	27	12	44	19	59/41/0257
567-5	3/4	32	14	54	22	59/41/0258
567-6	1	42	16	66	28	59/41/0259



Geluidsdemper, uit sinterbrons, met messing zeskant en messing aansluiting (versterkte versie)

Model	Aansluiting G	SW	A	B	C	CA-nummer
567-0/M	M5	8	5	20	4	59/41/0260
567-1/M	1/8	12	6	24	7	59/41/0261
567-2/M	1/4	16	8	30	10	59/41/0262
567-3/M	3/8	18	9	35	11	59/41/0263
567-4/M	1/2	24	10	44	15	59/41/0264
567-5/M	3/4	30	10	50	20	59/41/0265
567-6/M	1	36	12	63	25	59/41/0266




Geluidsdemper, uit sinterbrons, lange versie (schroevendraaiermontage)

Model	Aansluiting G	SW	A	B	C	CA-nummer
568-1	1/8	-	5,5	21	8	59/41/0267
568-2	1/4	-	8,5	27	10	59/41/0268
568-3	3/8	-	11	36	15	59/41/0269
568-4	1/2	-	11	44	19	59/41/0270

Geluidsdemper

Hoog debiet geluidsdemper



Meerkamer geluidsdemper met hoge afblaas doorstroom; korte ontwikkelingstijd en grote verlaging van dB(A).

Ingangsdruk : Max. 6 bar
Medium- en omgevingstemperatuur : Max. 90° C

Hoog debiet geluidsdemper


Model	Aansluiting G	L	i	D	CA-nummer
570-1	1/2	103	14	80	59/41/0210
570-2	3/4	106	16	80	59/41/0211
570-3	1	134	18	110	59/41/0212
570-4	1 1/4	140	20	110	56/41/0213
570-5	1 1/2	172	24	150	59/41/0214
570-6	2	172	24	150	59/41/0215



Wisselstukken

572 Set met 3 schijven voor bouwgroote G 1/2 - G 3/4 59/41/0216


Sinterbrons-geluidsdemper - instelbaar



Geluidsdemper uit sinterbrons/messing, afblazen instelbaar door contraoer

Model	Aansluiting G	SW	A	B	CA-nummer
563-0	M5	8	4	16-21	59/41/0219
563-1	1/8	16	8	38-44	59/41/0220
563-2	1/4	16	9	39-45	59/41/0221
563-3	3/8	22	10	47-60	59/41/0222
563-4	1/2	22	11	48-61	59/41/0223

Roestvrij, stalen geluidsdemper



Model	Aansluiting G	SW	A	B	CA-nummer
562-0 ES	M5	8	4	16	59/41/0224
562-1 ES	1/8	13	6	25	59/41/0225
562-2 ES	1/4	16	8	33	59/41/0226
562-3 ES	3/8	19	9	40	59/41/0227
562-4 ES	1/2	24	10	47	59/41/0228